

# Accent Wall Paneling - Oak Blend



[www.reclaimedlumberproducts.com/product/accent-wall-paneling-oak-blend](http://www.reclaimedlumberproducts.com/product/accent-wall-paneling-oak-blend)



**Width:** 5" only width

**Length:** 10" to 123" (random length with mix of entire range/ no order guaranteed specific lengths) Orders under 300 square feet have all lengths under 8', and larger orders tend to have all longer lengths.

**Thickness:** 3/8" (tolerances +/- 5/32"). NOT sanded or machined on back side so more thickness variation than our other paneling products between individual boards. Backside is bandsawn. More variation within length & width of each plank for thickness and flatness.

**Type of Material:** Individual solid wood boards planks from reclaimed mixed oak blend with up to 5% other hardwood species. 100% recycled.

**Edges & Ends:** All edges fresh square cut and ripped to exact 5" width. NOT waste defected, and ends are not fresh square cut.

**Texture:** Full rough original patina and texture face with no sanding or machining on face. No sealer or stain/ raw unfinished wood. No faux distress or chemical treatment.

**Color:** Dull natural color variety mix. Most colors honey brown, tan, or grey. Less variety in color and patina than our other paneling products.

**Other Processing:** Pressure washed, metal detected, kiln dried to 6-8% & sterilized at 160°.

## Installation Tips:

- Acclimate wood to local ambient moisture before installing.
- Install over solid continuous backing (preferably OSB or plywood) with PL Polyurethane Construction Adhesive and 18 gauge brad nails. Use as few of nails as possible. If backing is light colored paint black first.
- DO NOT make yourself dependent on any particular color or length to finish project. This product is not sold where special requests can be made for specific requirements; it is random blend sold by the square foot with no guarantee on ratio of colors or sizes. The best way to maintain random variety is before starting project unpack all boxes and sort into stacks of similar lengths and colors; when half of the project is complete then half of each stack should be used. As you proceed through the project if you notice one size is not being proportionally used according to progression then slightly adjust your consumption accordingly.
- Use techniques similar to installing random length wood flooring. Avoid joints close to each other, in predictable stair step pattern, or in alternate "H" pattern. Be sure to cut all ends square before installing.
- To avoid excess waste when one gets to the end of a row don't make cut-off pieces that cannot be reused. If one needs an 8" long board one would be better cutting it from a 20" piece than a 12" piece because the leftover could be reused.
- When ordering it is always cheaper to have material leftover than to order a small quantity at a higher price per square foot at the end of the job. All material is sold in 25 sf increments according to random size blend specifications. Things that will increase a waste factor are: small jobs with a lot of perimeter relative to field coverage, customer with expectations on color or texture requirements where they reject boards based on appearance, creating a pattern or specific size requirements,
- Not recommended for exterior, structural requirements, or high humidity applications. To protect, make easier to clean, lock in splinters or dust, then it is recommended to use a sealer. Always test your stain and finish before applying. It is your choice what to use, and how you do it could drastically change the appearance. Stain or dyes can mute the variation or push the overall color tone to a more predictable color. Water based finishes over solvent based finishes tend to go on more clear and change the color the least. Solvent based lacquers or tung oil will enhance and darken the look. Hand sanding with a sponge between sprayed on coats will give the smoothest feel and texture.